



5 é / Descriptions

(8)2 * @ 8 ©%². Ä å 3 5 9, +: % -eO P ' / òž ¥ / Ì Ä Ä³ o z ô y³ o z Š
 Ä å 3 5 9, + :ož ¥ / Ì Ä - 90• - vo• y 90• y vo• ½o• ? è ^ _ ¾ ' ^
 k G ' / ¶ k ä |ª W •ož
 (8)2 * @ 8 J *, 4 ~ (2 / x k Ù Q ¬ }%² Š y%² k • â ç • l k W •
 ¶ U ´ ož

□ª / Features


< Ä å S S 3 5 9, +: z
 < *, 4 ~ (2 / x z
 < Ä å “ ‘ z
 < M y y ' z
 < Ý 4² Á v v ' z
 < Ý 4 g 2 v v '
 < —) í D } ož

Ð ÷ / Applications

% -eO Y ÿ U - P Á k % -eO ü ` Ò U - P Á ož
 9 O T M R K R O Z N O [S O U T X K I N G X M K G H R K H R G _ Z S K X X _ X K / G I G X M Y K O G T H M R K K H R G O Z Z

À¹ € Ð Ô · ¢

h Þ y Š 8 P < Š > Q 4 Q 4) P < > [, k N / e / Ì Ü ¬ t k / Ì 3 o W
 • ož ò ç P } µ D k Š 8 À 1 ož



- ÚZ	- df	- a ¢
6 OT 4[SHKX6 OT 4GSK		6 OT *KYIXOVZOUT
	VDD	> €
	- 4 *	/ ìª kN P / ¿ â
	< 3	

3. Absolute Maximum Ratings(Ta=25℃ ;)

@ f/Parameter	... Z/Symbol	f > /Value	% y/Unit
V _{DD} input pin voltage	V _{IN}	-0.3 to +8	V
V _{VM} input pin voltage	V _{VM}	-8 to +10	V
Maximum Junction Temperature	T _J	-40 to +145	
Storage Temperature	T _{stg}	-55 to +145	
ESD g HBM Mode h	ESD	f 4000	V


4. Electrical Characteristics(Unless otherwise specified,Ta=25℃ ;)

@ f Parameter	... Z Symbol	y i Ú ^ Test Condition	Â 4 > Min	Á ° > Typ	Â Ý > Max	% y Unit
Power supply						
Supply Voltage	V _{DD}		0		6	V
Charger input voltage	V _M		-6		6	V
Detection voltage						
Overcharge Detection Voltage	V _{OCV}		4.25	4.3	4.35	V
Overcharge Release Voltage	V _{OCR}		4.04	4.10	4.16	V
Overdischarge Detection Voltage	V _{ODV}		2.30	2.40	2.50	V
Overdischarge Release Voltage	V _{ODR}		2.90	3.00	3.10	V
Detection current						
Overdischarge Current Detection	I _{OCI}		9	11.5	14	A
Load Short-Circuiting Detection	I _{SHORT}		15	25	35	A
Overcharge Current Detection	I _{CHA}		7	10	13	A
Static current						
Current Consumption in Normal Operation	I _{OPe}	V _M =0V		3.5	7	A
Current Consumption in Dormancy	I _{PDN}	V _{DD} =1.8V		0.6	1.5	A
Pull-up and Pull-down Current from VM						
Internal pull-up current	I _{PU}			14		A
Internal pull-down current	I _{PD}	V _M =1V		14		A
Equivalent FET on Resistance						
Equivalent FET on Resistance	R _{DS}	I _{VM} =1A	12.5	16	18	m

Electrical Characteristics(Ta=25 ;)

@ f Parameter	... Z Symbol	y i Ú ^ Test Condition	Â 4 > Min	Á ° > Typ	Â Ý > Max	% y Unit
Over temperature protection						
Over-temperature protection	OTP			145		
Over-temperature protection release temperature	OTPR			120		
Detection delay						
Overcharge Voltage Detection Delay Time	T _{Ocv}			100		ms
Overdischarge Voltage Detection Delay Time	T _{ODV}			100		ms
Overdischarge Current1 Detection Delay Time	T _{IOV1}			8		ms
Overdischarge Current2 Detection Delay Time	T _{IOV2}			2		ms
Load Short-Circuiting Detection Delay Time	T _{SHORT}			150		ms

Functionl Block Diagram



× 5 é	Functional Description
-------	------------------------



↳ Ô — ó Z Charger Detection


$\phi \hat{O} 9 y \hat{U} \acute{A} P y - \sim, k 3 < 3' 9 4 9^{\wedge} 9 - \sim y 9 <$ $) . ' k \phi P$
 $9 \acute{Y} 9^{\wedge} 9 y y 9 <$ $5^* < k (8) 2$ $* @ 8 1 K y y \hat{U} \acute{A} o \check{z}$

< Ô 1 ↳ Ô × 0V Battery Charging Function


$U Y < - k P 9 z 9 < k - / \grave{I} \mu g 2 \hat{U} \acute{A} k 4 \check{z} 3 5 9 \bullet \bullet k / \grave{I}^* \} 8 \hat{a}' - o \check{z}$
 $P 9 z 9 < k - v \acute{Y} 9 S' k Y^2 P y / \grave{I} C^{\circ} o \check{z}$

Timing Chart


Overdischarge Charging Normal Operation.



Ø α =) ¢ / Package Dimensions




, M y f / Marking Instructions



^a ¢ y
(8 y , [W A
 * y ° Z W A
 y ŷ D Z W A k š ŷ D Z J



šWD t... • Ž Ć (x /) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6



^a Ć y

10• Ä ½ “ † 150 ½180 - k ž • 60 ½90sec;

20• Q > “ † 245 r5 - k ž • 4 Ò 5 r0.5sec;

30•D N ò i Ò 0 , † 2 ½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“ † y 260 r5 -

ž • y 10 r1 sec.

Temp.:260±5

Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit Åmm³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
DFN3×3B-8L	5,000	2	10,000	6	60,000	13 s ×12	360×360×50	380×335×366

„Đ y f / Notices

Î † U ^ ñ Ä ' Î ® I c ¯ ² Á Ò Ć ³ Ø ož

All information provided in this document is subject to legal disclaimers.