





Rev.A Jan.-2018


Ultrafast Recovery rectifier bridge in a GBJ Plastic Package.


Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	600	V
Maximum RMS Voltage	V_{RMS}	420	V
Maximum DC Blocking Voltage	V_{DC}	600	V
	$I_{(AV)}$	4×30	A
	I_{FSM}	250	A
	R_{JC}	0.6	/W
	T_J	150	
	T_{stg}	-55 150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V_R	$I_R=1mA$	600	680		V
Forward Voltage	V_F	$I_F=5A \quad T_C=25$		1.32	1.45	V
		$I_F=5A \quad T_C=125$		0.90	1.25	
		$I_F=15A \quad T_C=25$		1.90	2.25	
		$I_F=15A \quad T_C=125$		1.26	1.65	
		$I_F=30A \quad T_C=25$		2.35	2.65	
		$I_F=30A \quad T_C=125$		1.65	2.15	
Instantaneous Reverse Current	I_R Note 1	$V_R=600V \quad T_a=25$			10	A
		$V_R=600V \quad T_a=125$			500	
Reverse Recovery Time	t_{rr}	$I_F=0.5A \quad I_{RR}=0.25A$ $I_R=1.0A$		40	50	ns



GBJ






GBJ3006SF

Note:

GBJ3006SF

Product Type

Lot No. Code, code change with Lot No.



Note:

- 1

25 150

60 90sec;
- 2

255 5

5 0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255 5

, Duration:5 0.5sec.
3. Cooling Speed: 2~10

/sec.

270 5

10 1 sec.

Temp.:270±5

Time:10±1 sec

/ BULK

Package Type	Units					Dimension (unit mm ³)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
GBJ	-	-	200	10	2000	-	255×145×48	310×270×250

/ TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
GBJ	15	40	600	2	1200	471×42×10	500×190×105	525×210×245